



Declaration of Performance (DoP)

| No. F305C-CPR-160407 | |
|---|--|
| Product Type: | Roomheaters fired by solid fuel |
| Type, batch or serial number: | Jøtul F 305C Series (Jøtul F 305C B, Jøtul F 305C LL, Jøtul F 305C SL) |
| Intended use of the product: | Roomheater burning solid fuel without water supply |
| Name and Address of the manufacturer: | Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no |
| AVCP: <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i> | System 3 |
| Notified body: | Danish Technological Institute |
| NB-No: | 1235 |
| Test report no: | 300-ELAB-2186-EN |
| Declared performance: | |
| Harmonized technical specification | EN 13240:2001/A2:2004/AC:2007 |
| Essential characteristics | Performance |
| Fuel | Wood logs |
| Fire safety | |
| Reaction to fire | A1 |
| Distance to combustible materials | Minimum distances, in mm Rear = 200 Sides = 300 Corner = 100 Front = 1000 <i>See also the installation instructions</i> |
| Risk of burning fuel falling out | No |
| Emission of combustion products | CO [0,06 %] NOx [85 mg/m ³] OGC [64 mgC/m ³] PM [7 mg/m ³] |
| Surface temperature | Pass |
| Electrical safety | - |
| Cleanability | Pass |
| Maximum water operating pressure | - |
| Flue gas temperature at nominal heat output | T [261°C] |
| Mechanical resistance (to carry a chimney/flue) | NPD |
| Thermal output | |
| Normal heat output | 7 kW |
| Room heating output | - kW |
| Water heating output | -*kW |
| Energy efficiency | η [79%] |

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.


Signed on behalf of the manufacturer:

Peter Sørensen
R&D Manager

(Name and function)

Fredrikstad, 07.04.2016

(Place and date of issue)



(Signature)