



## Declaration of Performance (DoP)

<b>No. F100 DE -CPR-130826</b>	
<b>Product Type:</b>	Roomheaters fired by solid fuel
<b>Type, batch or serial number:</b>	<b>Jøtul F 100 DE</b>
<b>Intended use of the product:</b>	Roomheater burning solid fuel without water supply
<b>Name and Address of the manufacturer:</b>	Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no
<b>AVCP:</b> <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	System 3
<b>Notified body:</b>	RWE Power AG, Feuerstättenprüfstelle
NB-No:	1427
Test report no:	FSPS-Wa 1943-EN
<b>Declared performance:</b>	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm Rear = 400 Sides = 500 Corner = 300 Front = 800 <i>See also the installation instructions</i>
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,12 %] NOx [116 mg/m <sup>3</sup> ] OGC [220 mgC/m <sup>3</sup> ] PM [27 mg/m <sup>3</sup> ]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [294°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	5 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [78%]

**Declaration:**

**The performance of the product in conformity with the declared performance.**

**This declaration of performance is issued under the sole responsibility of the manufacturer.**

**Signed on behalf of the manufacturer:**

Tom J. Berglind

R&D Manager


---

*(Name and function)*

Fredrikstad, August 26th 2013

---

*(Place and date of issue)*

  
*(Signature)*