

Declaration of Performance (DoP)

| No. F145-CPR-160501 | |
|---|---|
| Product Type: | Roomheaters fired by solid fuel |
| Type, batch or serial number: | Jøtul F 145 and Jøtul F 145 S |
| Intended use of the product: | Roomheater burning solid fuel without water supply |
| Name and Address of the manufacturer: | Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no |
| AVCP: <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i> | System 3 |
| Notified body: NB-No: Test report no: | Danish Technological Institute 1235 300-ELAB-0962-EN |
| Declared performance: | |
| Harmonized technical specification | EN 13240:2001/A2:2004/AC:2007 |
| Essential characteristics | Performance |
| Fire safety Reaction to fire Distance to combustible materials | A1 Minimum distances, in mm Rear = 300 Sides = 300 Front = 850 Other safety distances <i>See the installation instructions</i> |
| Risk of burning fuel falling out | No |
| Emission of combustion products | CO [0,09 %] PM [31 mg/m ³] |
| Surface temperature | Pass |
| Electrical safety | - |
| Cleanability | Pass |
| Maximum water operating pressure | - |
| Flue gas temperature at nominal heat output | T [269°C] |
| Mechanical resistance (to carry a chimney/flue) | NPD |
| Thermal output Normal heat output Room heating output Water heating output | 4 kW - kW -*kW |
| Energy efficiency | η [77%] |

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Anna K. Øren

R&D manager

(Name and function)

Fredrikstad, March 1st, 2018

(Place and date of issue)



(Signature)

Jøtul AS, 01.03.18 - Rev. 2